Revision: 05.08.2020



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HILCO PIPEWELD 6010
- · CAS Number: -
- · EINECS Number: -
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Shielded Metal Arc Welding Electrode

The product is a manufactured article in the sense of Article 3 No. 3, 1907/2006/EC (REACh). The purpose of the present safety data sheet is therefore to provide instruction on safe usage of the product.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

info@hilco-welding.com

Hilarius Haarlem Holland B.V. Emrikweg 7 2031 BT Haarlem Tel.: +31 (0) 23 531 91 00 www.hilco-welding.com

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The Product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

- · 2.2 Label elements -
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

EU



according to 1907/2006/EC, Article 31

Version number 20 Revision: 05.08.2020

Trade name: HILCO PIPEWELD 6010

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

•	D	a	ng	уe	r	ou	IS	(con	ıp	OI	ιе	nts	•

CAS: 7439-96-5 manganese substance with a Community workplace exposure limit 0.1-2.5% EINECS: 231-105-1 Reg.nr.: 01-2119449803-34-XXXX

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Seek medical treatment.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters

For deletion of fire just use dry powders. Don't use any water or halogenated containing extinguishing agents

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- · **6.2 Environmental precautions:** No special measures required.
- · 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure that suitable extractors are available on processing machines
- · Information about fire and explosion protection: No special measures required.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Version number 20 Revision: 05.08.2020

Trade name: HILCO PIPEWELD 6010

(Contd. of page 2)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

7439-96-5 manganese

IOELV Long-term value: 0.2* 0.05** mg/m³ as Mn; *inhalable, **respirable fraction

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Filter P2
- · Protection of hands:

EN 12477

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid

Colour: According to product specification

Odour: OdourlessOdour threshold: Not determined.

pH-value: Not applicable.Flash point: Not applicable.

· Flammability (solid, gas): Not determined.

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Version number 20 Revision: 05.08.2020

Trade name: HILCO PIPEWELD 6010

Upper: Not determined.

Density: Not determined.

Relative density Not determined.

Vapour density Not applicable.

Evaporation rate Not applicable.

water: Insoluble.

Partition coefficient: n-octanol/water: Not determined.

Partition coefficient: n-octanol/water: Not determined
 Dynamic: Not applicable.
 Kinematic: Not applicable.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Not hazardous for water.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Version number 20 Revision: 05.08.2020

Trade name: HILCO PIPEWELD 6010

(Contd. of page 4)

- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must be specially treated adhering to official regulations.
- · European waste catalogue

12 01 13 welding wastes

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	Void
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	-
•	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



according to 1907/2006/EC, Article 31

Version number 20 Revision: 05.08.2020

Trade name: HILCO PIPEWELD 6010

(Contd. of page 5)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Recommendations for Exposure Scenarios, Risk Management Measures and to identify Operational

Recommendations for Exposure scenarios, Risk wanagement weasures and to identify Operational Conditions under which metals, alloys and metallic articles may be safely welded.

Welding/Brazing produces fumes which can affect human health and the environment. Fumes are a varying mixture of eirborne gases and fine particles which, if inhaled or swallowed, constitute a health hazard. The degree of risk will depend on the composition of the fume, concentration of the fume and duration of exposure. The fume composition is dependent upon the material being worked, the process and consumables being used, coatings on the work such as paint, galvanizing or plating, oil or contaminants from cleaning and degreasing activities. A systematic approach to the assessment of exposure is necessary, taking into account the particular circumstances for the operator and ancillary worker that can be exposed.

Considering the emission of fumes when welding, brazing or cutting of metals, it is recommended to (1) arrange risk management measures through applying general information and guidelines provided by this exposure scenario and (2) using the information provided by the Safety Data Sheet, issued in accordance with REACH, by the welding consumable manufacturer.

The employer shall ensure that the risk from welding fumes to the safety and health of workers is eliminated or reduced to a minimum. The following principle shall be applied:

1- Select the applicable process/material combinations with the lowest class, whenever possible.

2- Set welding process with the lowest emission parameter.

3- Apply the relevant collective protective measure in accordance with class number. In general, the use of PPE is taken into account after all other measures is applied.

4- Wear the relevant personal protective equipment in accordance with the duty cycle.

In addition, compliance with the National Regulations regarding the exposure to welding fumes of welders and related personnel shall be

verified.

In the table "Risk Management Measures for individual process / material combinations" below, reference is made to the following standards for collective and personal protection measures:

ISO 4063

EN ISO 15012-1:2004

EN ISO 15012-2:2008

EN 149:2001

Respiratory protective devices - Filtering half masks to protect against particles - Requirements, testing, marking (FFP1 - FFP2 - FFP3)

EN 1835:2000

EN 12941:1998

EN 12941:1998

EN 12941:1998

Respiratory protective devices. Light duty construction compressed air line breathing apparatus incorporating a helmet or a hood. Requirements, testing, marking (LDH1 - LDH2 - LDH3).

Respiratory protective devices. Powered filtering devices incorporating a helmet or a hood. Requirements, testing, marking (LDH1 - LDH2 - LDH3).

Respiratory protective devices. Powered filtering devices incorporating a helmet or a hood. Requirements, testing, marking (LDH1 - LDH2 - LDH3).

Respiratory protective devices. Powered filtering devices incorporating a helmet or a hood. Requirements, testing, marking (LDH1 - LDH2 - LDH3).

Respiratory protective devices. Powered filtering devices incorporating a helmet or a hood.

Requirements, testing, marking (TH1 - TH2 - TH3).

EN 143:2000

Respiratory protective devices. Particle filters — Requirements, testing, marking (P1, P2, P3)

Article 6.2 on the protection of the health and safety of workers from the risks related to chemical agents at work

Article 6:2 on the protection of the insular and agents at work
Benutzung von Atemschutzgeräten (Berufsgenossenschaftliche Regel für Sicherheit und Gesundheit bei der Arbeit)
Schweisstechnische Arbeiten (Technische Regeln für Gefahrstoffe) BGR 190

TRGS 528

- Also in the table "Risk Management Measures for individual process / material combinations", reference is made to footnotes.

 The description of these footnotes:

 Class: approximate ranking to mitigate risk by selecting process/material combinations with the lowest value. Identified collective and individual risk management measures shall be applied

 Personal Protective Equipment (PPE) required avoiding exceeding the National Exposure Limit Value (DC: Duty cycle expressed on 8
- , ral Ventilation (GV) Low. With additional Local Exhaust Ventilation (LEV) and extracted air to the outside, the GV or LEV capacity
- may be reduced to 1/5 of the original requirement.

 General Ventilation (GV) Medium (double compared to Low)

- General Vertilation (GV) Medium (double compared to Low)
 Filtrating half mask (FFP2)
 When an alloyed consumable is used, measures from "Class V" are required
 General Vertilation (GV) Low. When no Local Exhaust Vertilation, the ventilation requirement is 5-fold
 Filtrating half mask (FFP3), helmet with powered filters (TH2/P2), or helmet with powered filters (TH2/P2), or helmet with powered filters, the compared to the surrounded area, is
 maintained.

- maintained
 Local Exhaust Ventilation (LEV) High, extraction at source (includes table, hood, arm or torch extraction)
 Helmetl with powered filters (TH3/P3), or helmet with external air supply (LDH3)
 Local Exhaust Ventilation (LEV) Low, extraction at source (includes table, hood, arm or torch extraction)
 Local Exhaust Ventilation (LEV) Medium, extraction at source (includes table, hood, arm or torch extraction)
 Recommended measures to comply with national maximum allowable limits. Extracted fumes, for all materials except unalloyed steel and aluminium, shall be filtered before release in the outside environment.
 A confined space, despite its name, is not necessarily small. Examples of confined spaces include ship, silos, vats, utility vaults, tanks, etc. Improved helmet, designed to avoid direct flow of welding fumes inside

- Not applicable Not recommended



according to 1907/2006/EC, Article 31

Version number 20

Trade name: HILCO PIPEWELD 6010

(Contd. of page 6)

Revision: 05.08.2020

Welding Exposure Scenario WES - ENGL

EWA2011

Risk Management Measures for individual process \emph{I} base material combinations

Class ¹	Process (according to ISO 4063)	Base Materials	Remarks	Ventilation / Extraction / Filtration ¹⁴	PPE ² DC<15%	PPE ² DC>15%
	(according to 150 4005)	Waterials	Non-confined sp	ace ¹⁶	DC 11370	DC= 1370
	GTAW 141		i i i i i i i i i i i i i i i i i i i	I		1
	SAW 12					
	Autogeneous 3		Except Aluminium	GV low ³	n.r.	n.r.
	PAW 15					
	ESW/EGW 72/73					
	Resistance 2					
	Stud welding 78					
	Solid state 521					
	Gases Brazing 9		Except Cd- allovs	GV low ³	n.r.	n.r.
П	GTAW 141		n.a.	GV medium ⁴	n.a.	FFP2°
-iii	MMAW 111		Except Be-, V- , Mn-,	GV mediam	II.a.	11112
	1011017-000	[All	Ni- alloys and			
			Stainless ⁶	GV low ⁷	Improved	FFP2 ⁵
	FCAW 136/137	All	Except Stainless and	LEV low ¹²	helmet16	12
	130/13/	\ \frac{1}{2}	Ni- alloys 6	22 100	Heimet	
	GMAW 131/135	All	Except Cu-, Be-, V-	-		
	131/130	10"	allovs ⁶			
	Powder Plasma Arc 152	All	Except Be-, V-, Cu-,	1		
	1 owder riasina / 40 / 702	' "	Mn-, Ni-alloys and			
			Stainless 6			
IV	All processes class I	Painted /	No Pb containing	GV low ³	_	FFP3, TH2/P2, or LDH2 ⁸
	, ai processes siass i	primed / oiled	primer	0.10.1	FFP2 ⁵	
	All processes class III	Painted /	No Pb containing	GV low '		
	, ai processes siass iii	primed / oiled	primer	LEV low12		
V	MMAW 111		n.a.	LEV high ¹⁰	TH3/P3,	TH3/P3
		Be-, and V-			LDH3 ¹¹	TH3/P3, LDH3 ¹¹
		alloys				
	FCAW 136/137					
		Mn- and Ni-				
		alloys				
	GMAW 131					
	Powder Plasma Arc 152					
		Mn-, Ni-, and				
		Cu- alloys				
VI	GMAW 131	Be-, and V-	n.a.	Reduced (negative) pressured area	TH3/P3, LDH3 ¹¹	TH3/P3, LDH3 ¹¹
	Powder Plasma Arc 152	alloys		LEV low12		
VII	Self shielded FCAW 114		Odd	5 1 1/ 2 3 1 9		
VII	Self shielded FCAVV 114		Cored wire, not	Reduced (negative) pressured area 9 LEV medium 13		
	Self shielded FCAW 114	alloyed steel	containing Ba	LEV medium	TU2/D2	TH3/P3.
	Self shielded FCAVV 114	Un-, high alloyed steel	Cored wire,	Reduced (negative) pressured area 9 LEV high ¹⁰	TH3/P3, LDH3 ¹¹	I DH3 ¹¹
	All	Painted /	containing Ba Paint / Primer	LEV nign	LDH3	LDH3
	All	primed	containing Pb			
	Arc Gouging and	All	n.a.	1	1	1
	Cutting 8	I All	In.a.		1	1
	Thermal Spray	All	n.a.	1	1	1
	Gases Brazing 9		n.a.	1	1	
	Gases brazing 9		n.a. :losed system or Confi	lood en aco ¹⁵		
	Laser Welding 52		Closed system or Confi	GV medium ⁴	n.a.	In.a.
	Laser Outting 84		Closed system	GV IIIeuluiii	11.a.	lii.a.
					1	1
1/111	Electron Beam 51		0		LDH3 ¹¹	LDUST
VIII	All	All	Confined space	LEV high ¹⁰ External air supply	LDH3	LDH3 ¹¹
	I	1	I	1	1	1

· Training hints -

· Abbreviations and acronyms:

NCEC - National Chemical Emergency Centre (=Carechem24)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances





according to 1907/2006/EC, Article 31

Version number 20 Revision: 05.08.2020

Trade name: HILCO PIPEWELD 6010

(Contd. of page 7)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.

ELI