

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **HILCO HILCHROME 600**

CAS Number: -

EINECS Number: -

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

### Application of the substance / the mixture

Shielded Metal Arc Welding Electrode

The product is a manufactured article in the sense of Article 3 No. 3, 1907/2006/EC (REACH). The purpose of the present safety data sheet is therefore to provide instruction on safe usage of the product.

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

Hilarius Haarlem Holland B.V.

Emrikweg 7

2031 BT Haarlem

Tel.: +31 (0) 23 531 91 00

[www.hilco-welding.com](http://www.hilco-welding.com)

[info@hilco-welding.com](mailto:info@hilco-welding.com)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

The Product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-00-7 Reg.nr.: 01-2119438727-29-XXXX	nickel ⚠ Carc. 2, H351; STOT RE 1, H372 ⚠ Skin Sens. 1, H317	25-50%
CAS: 7440-47-3 EINECS: 231-157-5 Reg.nr.: 01-2119485652-31-XXXX	chromium substance with a Community workplace exposure limit	5-12.5%
CAS: 13775-53-6 EINECS: 237-410-6 Index number: 009-016-00-2	trisodium hexafluoroaluminate ⚠ STOT RE 1, H372 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H332	5-12.5%
CAS: 1344-09-8 EINECS: 215-687-4 Reg.nr.: 01-2119448725-31-XXXX	Silicic acid, sodium salt ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318 ⚠ STOT SE 3, H335	5-12.5%
CAS: 7439-96-5 EINECS: 231-105-1 Reg.nr.: 01-2119449803-34-XXXX	manganese substance with a Community workplace exposure limit	5-12.5%
CAS: 513-77-9 EINECS: 208-167-3 Index number: 056-003-00-2 Reg.nr.: 01-2119489177-25-XXXX	barium carbonate ⚠ Acute Tox. 4, H302	0.1-2.5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### Description of first aid measures

**General information:** No special measures required.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Generally the product does not irritate the skin.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** Seek medical treatment.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:** Suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### 5.3 Advice for firefighters

For deletion of fire just use dry powders. Don't use any water or halogenated containing extinguishing agents

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

- **Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Use respiratory protective device against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Pick up mechanically.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure that suitable extractors are available on processing machines
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

### 7440-47-3 chromium

IOELV	Long-term value: 2 mg/m <sup>3</sup> as Cr
-------	---

### 7439-96-5 manganese

IOELV	Long-term value: 0.2 * 0.05** mg/m <sup>3</sup> as Mn; *inhalable, **respirable fraction
-------	---

### 513-77-9 barium carbonate

IOELV	Long-term value: 0.5 mg/m <sup>3</sup> as Ba
-------	---

- **DNELs**

### 13775-53-6 trisodium hexafluoroaluminate

Dermal	long-term (systemic)	510 mg/kg (Consumer) 1,020 mg/kg (Worker)
	Inhalative	Long term (local) 0.025 mg/m <sup>3</sup> (Consumer) 0.1 mg/m <sup>3</sup> (Worker)
	Acute (systemic)	74.5 mg/m <sup>3</sup> (Consumer) 99.8 mg/m <sup>3</sup> (Worker)

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

	Acute (local)	74.5 mg/m <sup>3</sup> (Consumer) 99.8 mg/m <sup>3</sup> (Worker)
--	---------------	--

## · PNECs

### 13775-53-6 trisodium hexafluoroaluminate

Water	1.4 mg/l (Sea Water) 0.2 mg/l (Sweet Water)
Sediment	214 mg/kg (Sea Water) 30.5 mg/kg (Sweet Water)
Soil	500 mg/kg (Soil)
sewage treatment plant	8.7 mg/l (STP)

· **Additional information:** The lists valid during the making were used as basis.

## · 8.2 Exposure controls

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:** Filter P2

· **Protection of hands:**

Leather gloves

EN 12477

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Safety glasses

· **Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

· **General Information**

· **Appearance:**

**Form:**

Solid

**Colour:**

According to product specification

· **Odour:**

Odourless

· **Odour threshold:**

Not determined.

· **pH-value:**

Not applicable.

· **Flash point:**

Not applicable.

· **Flammability (solid, gas):**

Not determined.

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product does not present an explosion hazard.

· **Explosion limits:**

**Lower:**

Not determined.

**Upper:**

Not determined.

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not applicable.
· <b>Evaporation rate</b>	Not applicable.
· <b>water:</b>	Insoluble.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Dynamic:</b>	Not applicable.
· <b>Kinematic:</b>	Not applicable.
· <b>Solids content:</b>	100.0 %
· <b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Attacks materials containing glass and silicate.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### LD/LC50 values relevant for classification:

#### 13775-53-6 trisodium hexafluoroaluminate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,100 mg/kg (rabbit)
Inhalative	LC50	4.47 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

#### 13775-53-6 trisodium hexafluoroaluminate

LC50 (static)	99 mg/l (Danio rerio)
EC50 (static)	156 mg/l (Daphnia magna)
	>160 mg/l (Soil Bacterial)
NOEC (static)	1 mg/l (Pseudokirchneriella subcapitata)
Water plant toxicity	8.8 mg/l (Pseudokirchneriella subcapitata)

### 12.2 Persistence and degradability No further relevant information available.

### 12.3 Bioaccumulative potential No further relevant information available.

### 12.4 Mobility in soil No further relevant information available.

#### Additional ecological information:

#### General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

### 12.5 Results of PBT and vPvB assessment

#### PBT: Not applicable.

#### vPvB: Not applicable.

### 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation Must be specially treated adhering to official regulations.

#### European waste catalogue

12 01 13 welding wastes

#### Uncleaned packaging:

#### Recommendation: Disposal must be made according to official regulations.

## SECTION 14: Transport information

ADR, ADN, IMDG, IATA Void

### 14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

### 14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

### 14.4 Packing group

ADR, IMDG, IATA Void

### 14.5 Environmental hazards:

Marine pollutant: No

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

(Contd. of page )

- |   |  |
|---|--|
| · 14.6 Special precautions for user                                       | Not applicable.                                      |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable.                                      |
| · Transport/Additional information:                                       | Not dangerous according to the above specifications. |
| · UN "Model Regulation":  | -<br>Void  |

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
No further relevant information available.
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 27
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Safety data sheet

### according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

Welding Exposure Scenario WES - ENGL

EWA2011

#### Recommendations for Exposure Scenarios, Risk Management Measures and to identify Operational Conditions under which metals, alloys and metallic articles may be safely welded

Welding/Brazing produces fumes which can affect human health and the environment. Fumes are a varying mixture of airborne gases and fine particles which, if inhaled or swallowed, constitute a health hazard. The degree of risk will depend on the composition of the fume, concentration of the fume and duration of exposure. The fume composition is dependent upon the material being worked, the process and consumables being used, coatings on the work such as paint, galvanizing or plating, oil or contaminants from cleaning and degreasing activities. A systematic approach to the assessment of exposure is necessary, taking into account the particular circumstances for the operator and ancillary worker that can be exposed.

Considering the emission of fumes when welding, brazing or cutting of metals, it is recommended to (1) arrange risk management measures through applying general information and guidelines provided by this exposure scenario and (2) using the information provided by the Safety Data Sheet, issued in accordance with REACH, by the welding consumable manufacturer.

The employer shall ensure that the risk from welding fumes to the safety and health of workers is eliminated or reduced to a minimum. The following principle shall be applied:

- 1- Select the applicable process/material combinations with the lowest class, whenever possible.
- 2- Set welding process with the lowest emission parameter.
- 3- Apply the relevant collective protective measure in accordance with class number. In general, the use of PPE is taken into account after all other measures is applied.
- 4- Wear the relevant personal protective equipment in accordance with the duty cycle.

In addition, compliance with the National Regulations regarding the exposure to welding fumes of welders and related personnel shall be verified.

In the table "Risk Management Measures for individual process / material combinations" below, reference is made to the following standards for collective and personal protection measures:

ISO 4063	Welding process Reference Numbers according to ISO 4063
EN ISO 15012-1:2004	Health and safety in welding and allied processes - Requirements testing and marking of equipment or air filtration - Part 1: Testing of the separation efficiency for welding fume
EN ISO 15012-2:2008	Health and safety in welding and allied processes - Requirements, testing and marking of equipment for air filtration - Part 2: Determination of the minimum air volume flow rate of captor hoods and nozzles
EN 149:2001	Respiratory protective devices - Filtering half masks to protect against particles - Requirements, testing, marking (FFP1 - FFP2 - FFP3)
EN 1835:2000	Respiratory protective devices. Light duty construction compressed air line breathing apparatus incorporating a helmet or a hood. Requirements, testing, marking (LDH1 - LDH2 - LDH3).
EN 12941:1998	Respiratory protective devices. Powered filtering devices incorporating a helmet or a hood. Requirements, testing, marking (TH1 - TH2 - TH3).
EN 143:2000	Respiratory protective devices — Particle filters — Requirements, testing, marking (P1, P2, P3)
Directive 1998/24/EC	Article 6.2 on the protection of the health and safety of workers from the risks related to chemical agents at work
BGR 190	Benutzung von Atemschutzgeräten (Berufsgenossenschaftliche Regel für Sicherheit und Gesundheit bei der Arbeit)
TRGS 528	Schweisstechnische Arbeiten (Technische Regeln für Gefahrstoffe)

Also in the table "Risk Management Measures for individual process / material combinations", reference is made to footnotes.

The description of these footnotes:

- <sup>1</sup> Class: approximate ranking to mitigate risk by selecting process/material combinations with the lowest value. Identified collective and individual risk management measures shall be applied
- <sup>2</sup> Personal Protective Equipment (PPE) required avoiding exceeding the National Exposure Limit Value (DC: Duty cycle expressed on 8 hours)
- <sup>3</sup> General Ventilation (GV) Low. With additional Local Exhaust Ventilation (LEV) and extracted air to the outside, the GV or LEV capacity may be reduced to 1/5 of the original requirement.
- <sup>4</sup> General Ventilation (GV) Medium (double compared to Low)
- <sup>5</sup> Filtering half mask (FFP2)
- <sup>6</sup> When an alloyed consumable is used, measures from "Class V" are required
- <sup>7</sup> General Ventilation (GV) Low. When no Local Exhaust Ventilation, the ventilation requirement is 5-fold
- <sup>8</sup> Filtering half mask (FFP3), helmet with powered filters (TH2/P2), or helmet with external air supply (LDH2)
- <sup>9</sup> Reduced (negative) pressured Area: A separate, ventilated area where reduced (negative) pressure, compared to the surrounded area, is maintained
- <sup>10</sup> Local Exhaust Ventilation (LEV) High, extraction at source (includes table, hood, arm or torch extraction)
- <sup>11</sup> Helmet with powered filters (TH3/P3), or helmet with external air supply (LDH3)
- <sup>12</sup> Local Exhaust Ventilation (LEV) Low, extraction at source (includes table, hood, arm or torch extraction)
- <sup>13</sup> Local Exhaust Ventilation (LEV) Medium, extraction at source (includes table, hood, arm or torch extraction)
- <sup>14</sup> Recommended measures to comply with national maximum allowable limits. Extracted fumes, for all materials except unalloyed steel and aluminium, shall be filtered before release in the outside environment.
- <sup>15</sup> A confined space, despite its name, is not necessarily small. Examples of confined spaces include ship, silos, vats, utility vaults, tanks, etc.
- <sup>16</sup> Improved helmet, designed to avoid direct flow of welding fumes inside
- <sup>n.a.</sup> Not applicable
- <sup>n.r.</sup> Not recommended

## Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

Welding Exposure Scenario WES - ENGL

EWA2011

Risk Management Measures for individual process / base material combinations

Class <sup>1</sup>	Process (according to ISO 4063)	Base Materials	Remarks	Ventilation / Extraction / Filtration <sup>14</sup>	PPE <sup>2</sup> DC<15%	PPE <sup>2</sup> DC>15%
Non-confined space <sup>15</sup>						
I	GTAW 141	All	Except Aluminium	GV low <sup>2</sup>	n.r.	n.r.
	SAW 12					
	Autogeneous 3					
	PAW 15					
	ESW/EGW 72/73					
	Resistance 2					
	Stud welding 78					
	Solid state 521					
Gases Brazing 9	All	Except Cd- alloys	GV low <sup>2</sup>	n.r.	n.r.	
II	GTAW 141	Aluminium	n.a.	GV medium <sup>4</sup>	n.a.	FFP2 <sup>8</sup>
III	MMAW 111	All	Except Be-, V-, Mn-, Ni- alloys and Stainless <sup>5</sup>	GV low <sup>7</sup> LEV low <sup>12</sup>	Improved helmet <sup>16</sup>	FFP2 <sup>8</sup>
	FCAW 136/137	All	Except Stainless and Ni- alloys <sup>5</sup>			
	GMAW 131/135	All	Except Cu-, Be-, V- alloys <sup>6</sup>			
	Powder Plasma Arc 152	All	Except Be-, V-, Cu-, Mn-, Ni-alloys and Stainless <sup>5</sup>			
IV	All processes class I	Painted / primed / oiled	No Pb containing primer	GV low <sup>2</sup>	FFP2 <sup>8</sup>	FFP3, TH2/P2, or LDH2 <sup>8</sup>
	All processes class III	Painted / primed / oiled	No Pb containing primer	GV low / LEV low <sup>12</sup>		
V	MMAW 111	Stainless, Ni-, Be-, and V- alloys	n.a.	LEV high <sup>10</sup>	TH3/P3, LDH3 <sup>11</sup>	TH3/P3, LDH3 <sup>11</sup>
	FCAW 136/137	Stainless, Mn- and Ni- alloys				
	GMAW 131	Cu- alloys				
	Powder Plasma Arc 152	Stainless, Mn-, Ni-, and Cu- alloys				
VI	GMAW 131	Be-, and V- alloys	n.a.	Reduced (negative) pressured area <sup>9</sup> LEV low <sup>12</sup>	TH3/P3, LDH3 <sup>11</sup>	TH3/P3, LDH3 <sup>11</sup>
	Powder Plasma Arc 152					
VII	Self shielded FCAW 114	Un-, high alloyed steel	Cored wire, not containing Ba	Reduced (negative) pressured area <sup>9</sup> LEV medium <sup>10</sup>	TH3/P3, LDH3 <sup>11</sup>	TH3/P3, LDH3 <sup>11</sup>
	Self shielded FCAW 114	Un-, high alloyed steel	Cored wire, containing Ba	Reduced (negative) pressured area <sup>9</sup> LEV high <sup>10</sup>		
	All	Painted / primed	Paint / Primer containing Pb			
	Arc Gouging and Cutting 8	All	n.a.			
	Thermal Spray	All	n.a.			
	Gases Brazing 9	Cd- alloys	n.a.			
Closed system or Confined space <sup>15</sup>						
I	Laser Welding 52	All	Closed system	GV medium <sup>4</sup>	n.a.	n.a.
	Laser Cutting 84					
	Electron Beam 51					
VIII	All	All	Confined space	LEV high <sup>10</sup> External air supply	LDH3 <sup>11</sup>	LDH3 <sup>11</sup>

### Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

# Safety data sheet

## according to 1907/2006/EC, Article 31

Version number 15

Revision: 25.08.2020

Trade name: HILCO HILCHROME 600

H411 Toxic to aquatic life with long lasting effects.

### Abbreviations and acronyms:

NCEC - National Chemical Emergency Centre (=Carechem24)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - inhalation – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

### \* Data compared to the previous version altered.